

PIG® Original SpillBlocker® Dike

PLR204 Ideal For Quick Spill Response, One 4" W x 10' L x 2.25" H Section

Confine and divert spills up to 2.25" deep with our customer-favorite dike. Others look the same but only PIG delivers durable two-part construction.

- Exclusive New Pig formulation features a tear-resistant top layer and a flexible, tacky bottom layer that seals tight to smooth surfaces and blocks liquids
- Other dikes may look similar, but only PIG SpillBlocker Dikes have two-layer construction for superior performance
- 2.25" height is great for containing smaller spills
- Fast protection for when a spill is heading right for your drain; just place dike in front of spill to contain liquid
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- Polyurethane material resists water, oils and many chemicals
- Reusable dike cleans easily with soap and water



Item#	Description	Dimensions	Weight
PLR204-YW	Yellow,	4" W x 10' L x 2.25" H	30 lbs.
PLR204-BK	Black,	4" W x 10' L x 2.25" H	30 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PLR204-YW	Yellow,	10.2cm W x 3m L x 5.7cm H	13.6 kg
PLR204-BK	Black,	10.2cm W x 3m L x 5.7cm H	13.6 kg

Specifications

Traffic	Non-Weight Bearing
Barrier Dimensions	One 4" W x 10' L x 2.25" H Section
Dimensions	4" W x 10' L x 2.25" H
Barrier Type	Urethane Blocker
Ideal For	Quick Spill Response
Install/Deploy Type	Temporary/Removable Barrier

Intended Use	Smooth Surfaces
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes
Storage Temp Range	Store Between 0°F and 120°F
Temperature Limit	Works from 0°F to 160°F up to 1 Year
Sold as	1 per box
Weight	30 lbs.
New Pig Patent	5,236,281
# per Pallet	32
Composition	Polyurethane
UNSPSC	24101907
Pigalog® Page Number	<u>Page 175</u>

Metric Equivalent

Dimensions	10.2cm W x 3m L x 5.7cm H
Weight	13.6 kg

Technical Information

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[PIG Spillblocker Dike Instructions](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com